

#### **M650H**


#### **SELF-CONTAINED LED LANTERN** FOR BUOYS AND MINOR **BEACONS, 2 TO 4+ NM RANGE**

The M650H is a cost effective, selfcontained, high-performance, lowmaintenance and easy-to-install solar LED marine lantern. The M650H features a replaceable battery pack that extends the service life beyond five years, reducing the total cost of ownership. Applications include: marine aids-to-navigation marking, marina lighting, dock lighting, and port lighting. To view performance in your installation location, visit carmanahmarine. com/selector.

- Standard IALA colours Red, Green, White, Yellow, Blue
- High-efficiency solar cells with bypass and blocking diode function. Maximum power point tracking (MPPT) for optimal energy collection
- Premium grade UV resistant, polycarbonate/polysiloxane copolymer body and lens material
- Colour-specific temperature corrected LED drivers provide consistent intensity under all operating conditions IP 68 rated. Double O-ring sealing with waterproof vent
- **SLA** battery
- Ventilated battery compartment
- Adjustable intensity and range
- Vertical divergence > 8º (FWHM)
- Programmable with On-Board User Interface, USB port, or optional wireless IR-Programmer
- Integrated event-log
- Optional ON/OFF switch
- Optional external charger
- Optionally integrated GPS synchronization














**BIRD DETERRENT** Stainless steel as standard. Tool-less installation and replacement.



**SOLAR MODULES** High-efficiency cells with bypass and blocking diode function. Maximum power point tracking (MPPT) for optimal energy collection.



**SLA BATTERY** Tool-less replaceable and recyclable best-in-class battery pack with extreme temperature range and 5-year life expectancy. On-board battery status feedback of Good, Charge, Low or Replace. True battery voltage shown.



**COLOUR INDICATOR** Protective bumper indicates LED colour.



Replaceable and recyclable NiMH batteries with extreme temperature range

and 5-year life expectancy.

**ON-BOARD USER INTER-**



**650 DEVICE MANAGER SOFTWARE** Check battery status,

change flash code, adjust light intensity and turn lantern off with optional mini IR (Infrared) programmer.



**IR CONTROLLER** Optional external ON/OFF switch.



**INSTALLATION** Easily adjusts to 2 3/8 inch, 60mm or 1 7/8 inch, 48 mm pole dimensions.



**BOTTOM COVER REMOVAL** TOOL Available as accessory.



**BARGE APPLICATION** For barge application, sector plates with open sectors of 112,5°, 135° and 225°.





**PHONE** 

310.522.9698



### **TECHNICAL SPECIFICATION M650H**





OPTICAL PERFORMANCE						
Maximum fixed intensity						
31 cd	45 cd	60 cd	52 cd	15 cd		

Note: Peak IALA intensity dependent on location. To view performance in your installation location, visit www.carmanahmarine.com/selector.

MAIN TECHNICAL SPECIFICATION				
Lens visual/Mechanical diameter	165 mm			
Lens material	UV stabilized Polycarbonate			
Light source	High Power Light Emitting Diode (LED)			
Vertical divergence	>8° (FWHM)			
Solar module	High efficiency cells; bypass and blocking diodes; MPPT			
Battery	Sealed Lead Acid			
Degree of ingress protection	IP 68			
Weight	1.58 kg			
Overall height	169 mm			
Overall width	176 mm dia.			
Installation	3 x M6 on 150 mm dia.			





### **ORDER OVERVIEW M650H**

OPTION MATRIX			
M650H Switched	ON/OFF switch		
M650H Unswitched	No ON/OFF switch		
M650H Switched GPS	Includes GPS synchronization & ON/OFF switch		
M650H Unswitched GPS	Includes GPS synchronization (no ON/OFF switch)		

ACCESSORIES			
57003	650 Bird Deterrent – Additional (1 ships with each lantern)		
57392	650 Bottom Cover Replacement Pack Switched		
57393	650 Bottom Cover Replacement Pack Unswitched		
59198	650 Bottom Cover Removal Tool		
72835	650 Battery Replacement Pack		
59188	650 International Wall Charger Assembly		
57394	650 USB Cable		
69899	IR (Infrared) Programmer		
38334	650 Standard Bolt Kit		
64407	650 Security Mounting Bolt Kit (Includes drivers)		
56578	650 Security Bolt and Nut Set (Drivers not included)		
53284	500/650 Security Key		
53285	500/650 Security Socket		

PRODUCT CODES						
Colour	M650H unswitched	M650H switched	M650H unswitched GPS	M650H switched GPS		
red	M650R	M650R-S	M650R-GPS	M650R-SGPS		
green	M650G	M650G-S	M650G-GPS	M650G-SGPS		
white	M650W	M650W-S	M650W-GPS	M650W-SGPS		
yellow	M650Y	M650Y-S	M650Y-GPS	M650Y-SGPS		
blue	M650B	M650B-S	M650B-GPS	M650B-SGPS		

